

Oxford Floorboards 21mm Solid Oak

Detailed Drawings & Specifications





Oxford Floorboards 21mm Solid Oak

The Oxford quite literally offers the best of both worlds: long length boards combined with a range of impressive widths to create a genuine yet bespoke floor of your choice, while giving the benefits of a modern flooring board at its best - exceptionally well machined for tight joins and ease of laying.

With its filled and sanded finish, tongue and groove end and stress grooves on the back face (giving increased stability), this is as close as you can get a solid floor to engineered!

- End-matched, prefilled and sanded, reducing the installation time
- Stress grooved to increase stability
- Longer length specification
- Character grade to create an interesting floor with features
- Delivered in 3 5 days, stock item













√ Technical Data

	Grade	Character. Virtually sap free (increased durability)
	Edge detail	Square shoulders, tongue & groove sides and ends. Stress grooves on back face.
	Supplied finish	Filled & sanded, unfinished
•	Recommended finish	Oiled or lacquered, a light sand recommended prior to finishing
	Wastage allowance	10% recommended
	Underfloor heating	Not suitable
	Density	800kg/m³ or 16kg/m² approx.
	Lengths (m)	Majority are 2.3 - 2.8, random
	Widths (mm)	160, 180, 200
	Acclimitisation	7 days minimum

✓ Application Instructions

- **Suggested applications** Ideal for any room in the house, with bathrooms and wet rooms being the exception, as this is not recommended. Also Oxford fits in with any style of house, the product is ideal for older properties where underfloor heating is not present. Designed to be structurally sound fitted directly to joists.
- **Fixing** Correct methods of laying and fixing Oak flooring are critical to both its look and its function. This product can be glued, secret nailed, face nailed or floated, for more information, click here, or scan below.







Oxford Floorboards

Profile drawing









